

Urethane Wood Flooring Adhesive - Plus Moisture Barrier

Section 1: Identification

1.1.Product name: Real Wood Cohesive

Urethane Wood Flooring Adhesive - Plus Moisture Barrier

1.2. Relevant use of the substance and restrictions on use:

Recommended use: Urethane Adhesive

Restrictions: N.A. 1.3. Supplier details:

> Real Wood Floors 1098 Chestnut Bend West Plains, MO 65775 www.realwoodfloors.com Phone: (877) 213-1851

Section 2: Hazards Identification

2.1. Hazard Statements

H315 Causes Skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eve irritation.

May cause allergy or asthma or breathing difficulties if inhaled. H334

H335 May cause respiratory irritation.

2.2. Precautionary Statements

Do not handle until safety precautions have been read and understood. P202

P264.2 Wash skin thoroughly after handling Wear protective gloves and eye protection. P280.1

P284 In case of inadequate ventilation, wear respiratory protection.

IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. P301+P310

IF ON SKIN: Wash with plenty of water. P302+P352.A

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep

at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

If experiencing respiratory symptoms: Call a POISON CENTER. P311.A+P342 P313+P333 If skin irritation or rash occurs: Get medical attention/advice. P362+P364 Take off contaminated clothing and wash it before use.

P405 Store locked up.

Dispose of contents / container in accordance with local / regional / P501

national / international regulations.

2.3. Classification System

HMIS rating (scale 0 - 4) HEALTH FLAMMABILITY REACTIVITY 1 0 1

Other Hazards None known



Urethane Wood Flooring Adhesive - Plus Moisture Barrier

GHS label elements Hazard pictograms:



Signal word: Danger

Section 3: Composition / Information on Ingredients

ComponentCAS NumberWeight Percent OSHA (PEL)ACGIH (TLV-TWA)MDI Isocyanate101-68-8<1%</td>0.020.005 ppmCalcium Carbonate1317-65-335-60%15 mg/m310 mg/m3

Section 4: First Aid Measures

4.1.Description of first aid measures

Eyes: Flush with large amounts of cool water for at least 15 minutes while holding

eyelid open. Seek medical attention.

Skin: Remove contaminated clothing. Wash the contaminated area with soap and

water. If rash or irritation or other symptoms persist, seek medical attention.

Inhalation: Remove to fresh air. If breathing has stopped initiate artificial respiration and

obtain immediate medical attention.

Ingestion: Do not induce vomiting. Do not give anything by mouth. Seek immediate medical

attention.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation Eye damage Skin irritation Erythema

4.3.Indication of any immediate medical attention and special treatment needed

Seek medical advice and take this safety data information if possible.

Section 5: Fire Fighting Measures

5.1. Extinguishing media

Pertinent extinguishing media are water and carbon dioxide gas.



Urethane Wood Flooring Adhesive - Plus Moisture Barrier

5.2. Specific hazards rising from the substance / mixture

Combustion of this product may yield irritating or toxic gases.

5.3. Advise for fire fighters

Use self-contained breathing apparatus. Wear protective clothing. Do not discharge contaminated extinguishing water into drains.

Section 6: Accidental Release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protective equipment.

6.2.Environmental Procedures

Prevent entry into drains and water courses.

6.3. Methods and material for containment and clean up

Absorbing material can be used such as dry sand or earth. Collect into containers for disposal.

6.4.reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

Section 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact and inhalation of vapors. Do not handle broken packaging without protective equipment.

7.2. Conditions for storage, including any incompatibilities

Store this product in a cool dry area, out of direct sunlight. Store in a well ventilated area away from all sources of ignition. There are no relevant incompatible materials.

7.3. Specific end use(s)

See section 1.2.

Section 8: Exposure Control / Personal Protection

8.1.Control parameters

Exposure parameters should fall under those listed in Section 3 of this safety data sheet.

8.2.Individual protection measures

Use in well ventilated areas only to maintain PEL / TLV levels below set exposure limits.

Due to the low V.O.C. nature of this product, respiratory protection is not normally required.

However, if PEL / TLV levels may potentially exceeded those listed in Section 3 of this safety data sheet, use NIOSH / MSHA approved respirator.

Eye Protection: Wear safety glasses or goggles as necessary to protect eyes.

Skin Contact: Protective gloves are recommended in situations when direct skin contact is unavoidable (nitrile, rubber or better).

Other Protective Equipment: Use other types of equipment as needed to help minimize contact.



Urethane Wood Flooring Adhesive - Plus Moisture Barrier

Section 9: Physical and Chemical Properties

9.1.Information on basic physical and chemical properties

Appearance and Odor: Creamy liquids / low odor

Solubility in Water: Insoluble

Evaporation Rate (Compared to Butyl Acetate as 1.0): <1.0

Boiling Point: >300F

pH: N/A

Vapor Density (Air = 1.0): >1.0 Volatile Organic Content: <30.0 g/l Vapor Pressure: <1 mm Hg @ 75F / 24C

Freezing Point: N/E

9.2. Other information

Section 10: Stability and Reactivity

10.1.Reactivity

This product is stable under normal conditions.

10.2.Chemical stability

This product is stable under normal conditions.

10.3. Possibility of hazardous reactions

No hazardous reactions in particular.

10.4. Conditions to avoid

This product is stable under normal conditions.

10.5.Incompatible materials

No incompatible groups noted.

10.6. Hazardous decomposition products

Decomposition in a fire may produce carbon monoxide (CO) and carbon dioxide (CO2).

Section 11: Toxicological Information

11.1.Information on toxicological effects

Detrimental health effects are not expected as long as correct industrial hygiene and safety protocols are followed.

Section 12: Ecological Information

12.1.Toxicity

No data available.

12.2.Persistence and degradability

There is no data on the degradability of this product.



Urethane Wood Flooring Adhesive - Plus Moisture Barrier

12.3.Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5.Results of PBT and vPvB assessment

No dada available.

12.6.Other adverse effects

No data available.

Section 13: Disposal Considerations

13.1. Waste treatment methods

Dispose of material in accordance with local, state and federal regulations.

Section 14: Transportation Information

14.1.UN number

Not applicable.

14.2.UN proper shipping name

Not applicable.

14.3. Transport Hazard classes

Not applicable.

14.4.Packaging group

Not applicable.

14.5. Environmental hazards

Environments pollutant: Not applicable

Marine pollutant: No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Section 15: Regulatory Information

Component CAS Number Weight Percent OSHA (PEL) ACGIH (TLV-TWA)

 MDI Isocyanate
 101-68-8
 <1%</th>
 0.02
 0.005 ppm

 Calcium Carbonate
 1317-65-3
 35-60%
 15 mg/m3 1
 10 mg/m3

TSCA

All components in these products are listed except where written as exempt.

SARA

Section 302: Extremely hazardous substances

None listed.

1098 Chestnut Bend West Plains, MO 65775 877.215.1831 realwoodfloors.com



Urethane Wood Flooring Adhesive - Plus Moisture Barrier

Section 304: Hazardous substances

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate) is listed.

Section 313: Toxic chemical list

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate) is listed.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA)

Substances listed

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate) is listed.

Clean Air Act (CAA)

Substances listed

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate) is listed.

Clean Water Act (CWA)

Substances listed

No substances listed.

USA – State Specific Information

California Proposition 65

Substances listed

No substances listed.

Massachusetts Right to Know

Substances listed

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate)

Calcium Carbonate

Pennsylvania Right to Know

Substances listed

MDI Isocyanate (4,4-Methylenediphenylene diisocyanate)

Calcium Carbonate

New Jersey Right to Know

Substances listed

Calcium Carbonate

Section 16: Other information

All information set forth herein is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy or completeness of this information. No responsibility for personal injury or property damage to sellers, users or third parties caused by these materials is assumed. Such sellers or users assume all risks associated with this material.